

TECHNICAL SPECIFICATION



Openable flat roof windows with flat glass top unit

FRE B600 + FGT B200

PANE	
Construction	4H-(32)-4-14,5-33.2
24 mm insulated glazing unit	■
Low-E coating	■
Gas	Argon
Toughened external glass	■
U_g -horizontal (W/m ² K)	1.30
Total solar energy transmittance: g	0.54
Light transmittance: τ_v	0.72
WINDOW	
$U_{rc,ref300^{\circ}}$ (W/m ² K)	0.87
$A_{rc,ref300^{\circ}}$ (m ²)	3.4
Watertightness	Class 9A
Air permeability	Class 3
Resistance to wind load	Class C3
Sound reduction	31 (-1,-2) dB
Reaction to fire	class B-s1, d0
Impact resistance	class 3
FINISH	
Interior: PVC (white)	RAL 9016
Exterior: Grey aluminium	RAL 7043

APPLICABLE

- In public or residential buildings
- In heated, inhabited rooms
- In roof pitch range of 2°-15° (5°-15° is recommended)

FEATURES

- Electrically openable window for flat roofs
- Attractive, flat glass exterior design
- Maintenance free, easy-to-wipe internal PVC surfaces
- Easy-to-clean coating on external glass
- scratch-free, 4 mm toughened glass cover
- Laminated internal glass
- Low energy insulating glass unit (inside)
- Max. opening: 200 mm (142 mm ventilation area)
- Preinstalled rain sensor
- Hidden motor
- Wall switch controller
- Fixing screws and brackets are included
- Easy installation
- 10-year guarantee

MATERIALS AND FINISH

- Extruded, white PVC, RAL 9016
- Insulating inserts in the PVC curb
- Lacquered aluminium, RAL 7043 (Top unit)

AVAILABLE SIZES AND DAYLIGHT AREA

Product code	Nominal size (roof opening)		External frame measurements		Lining measurements		Effective daylight area		
	Width	Length	Width	Length	Width	Length	Width	Length	A
	cm	cm	cm	cm	cm	cm	cm	cm	m ²
FRE 0606 B600	60	60	78	78	55.9	55.9	43.5	43.5	0.19
FRE 0808 B600	80	80	98	98	75.9	75.9	63.5	63.5	0.40
FRE 0609 B600	60	90	78	108	55.9	85.9	43.5	73.5	0.32
FRE 0909 B600	90	90	108	108	85.9	85.9	73.5	73.5	0.54
FRE 0912 B600	90	120	108	138	85.9	115.9	73.5	103.5	0.76
FRE 1010 B600	100	100	118	118	95.9	95.9	83.5	83.5	0.70
FRE 1015 B600	100	150	118	168	95.9	145.9	83.5	133.5	1.11
FRE 1212 B600	120	120	138	138	115.9	115.9	103.5	103.5	1.07

AVAILABLE SIZES

ACCESSORIES

SIZE CODE



0606

0609

0808

0909

ROOF OPENING (CM)

60X60

60X90

80X80

90X90

SIZE CODE



0912

1010

1015

1212

ROOF OPENING (CM)

90X120

100X100

100X150

120X120

FRC

Extra frame extension can be combined with FRC..F (frame extension with flange) when frame height exceeding 310 mm is required*
* One FRC..F can be combined with max three FRC extension curbs

FRC..F

Frame extension with flange – extends total frame height from 150 mm to 310 mm

FAF

Roofing material fixing kit ensures a safe joint between frame and roofing material

