## Flashing: EDS 0000





### New nera tion ouvell

## For flat roofing material up to 8 mm

- A perfect match with VELUX roof window
- Fast installation
- Maintenance-free and no corrosion
- Tested for extreme weather conditions
- VELUX guarantee

#### Flashing EDS 0000 features





Flashing material: Roof pitch: Aluminium 15°-90° Dark grey



Profile height: max 8 mm, Slate or roofing felt





Standard installation: **Red line level** 

#### Single and combi-flashings


		Flat roofing material: 8 mm
1		EDS
2		EBS
3		EKS
4		EKS7- + EDS
5	ſ	EFS
6		EFS22/32
7	Ţ	EDS (available from 2015)
8		ETS + EDS
9		ETS + ETS00- + EKS
10		EKX88
11		EES + EEX
12	10°	EAS
13	→+ a=160 mm	

#### **Technical drawing**


# 

#### **Technical specifications**

Material:	Aluminium alloys	
Aluminum thickness:	0,47 mm - 0,65 mm	
Coating thick:	Min 24 µm, according to EN 13523-1	
Gloss 60°:	30E, according to EN 13523-2	
Standard color:	Grey NCS S 7500-N, according to EN 13523-3	



#### Available flashing materials



#### Benefits





#### **Reliable and fast installation**

A perfect match - designed to fit the window precisely. Convenient, reliable, fast and easy installation. Saves time and money – and gives you satisfied customers.

#### Tested for extreme weather conditions

The VELUX flashings have been tested in our wind tunnel – the largest in Northern Europe. Your guarantee for a reliable and durable product.

#### **Discreet and attractive design**

The VELUX flashing design has been proven on millions of roofs world-wide. Pleasing aesthetics, no corrosion, and totally maintence-free. The wellknown VELUX quality you can trust.





Fast & easy to install



Perfect fit





Warranty

**Contact:** VELUX Denmark A/S Breltevej xx 2970 Hørsholm Support: 2323 4545

